INSTRUCTIONS FOR USE

SIKEZHAN 3-in-1 Universal Lubricant for PDR Tool Maintenance, 60 ml

1. Intended Use

SIKEZHAN 3-in-1 is a universal lubricant for cleaning, lubricating and protecting metal PDR tools made of high-carbon steel against corrosion, including tools with a protective coating produced by chemical blackening.

The lubricant helps remove surface contaminants, reduces friction between metal parts and forms a thin protective oil film that limits contact with moisture and helps prevent rust and corrosion.

2. Key Properties

Cleaning. Helps remove dust, old lubricant residue and surface contaminants from metal tool components.

Lubrication. Forms a thin oil film that reduces friction and wear on contacting metal surfaces.

Corrosion protection. Creates a protective barrier that reduces moisture exposure and helps prevent corrosion.

Protective coating care. May be used on chemically blackened tools after first checking compatibility with the specific coating.

3. Directions for Use

Step 1. Preparation. Before applying, remove dust, dirt and other particles from the tool using a clean, dry cloth. Make sure the tool surface is dry.

Step 2. Cleaning. Apply a small amount of lubricant to a clean, soft cloth or directly to the contaminated metal surface. Gently wipe the surface, paying particular attention to old lubricant residue and surface dirt. Repeat if necessary. Remove loosened dirt with a clean cloth. Do not use abrasives or stiff metal brushes that could damage the protective coating.

Step 3. Lubrication. Apply 1–2 drops to metal surfaces requiring lubrication. Spread evenly with a clean, soft cloth. Avoid overapplication, as excess lubricant may attract dust and dirt.

Step 4. Corrosion protection. To protect tools during storage, apply a few drops to a clean, soft cloth. Wipe metal surfaces evenly to form a thin protective layer. Remove excess lubricant, leaving a thin oil film. Pay particular attention to areas touched by hands or exposed to moisture. Before using a PDR tool, remove excess lubricant, especially from working tips and surfaces that may contact the vehicle body.

4. Safety Precautions

Use in a well-ventilated area. Avoid contact with eyes. Wear eye and face protection during use. Avoid prolonged skin contact. Wash hands thoroughly after use.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do, then continue rinsing. Seek medical attention immediately.

If swallowed: Do not induce vomiting. Seek medical attention immediately. Keep out of reach of children and pets.

5. Storage Conditions

Close the bottle cap tightly after use. Store upright in a cool, dry, well-ventilated place. Keep away from heat sources and open flames.

6. Composition

Mineral oil — 85%; synthetic oil — 10%; anti-wear additives — 3%; antioxidants — 1%; other ingredients — 1%.

7. Product Information

Brand: SIKEZHAN. Product name: 3-in-1 Universal Lubricant.

Intended use: Cleaning, lubrication and corrosion protection of high-carbon steel PDR tools.

Volume: 60 ml. Internal SKU: LUB-SKZ-60.

Manufacturer: Shenzhen Yiluoxi Trading Co., Ltd. Country of origin: China.

Manufacturing date: 24 September 2026. Expiration date: 23 September 2029.